



Antistatic polyurethane hose, super-light, microbe resistant + flame-retardant

### Applications

- flexible hose/ ducting for gases and for abrasive dust, powder, fibres
- extraction unit, dedusting system, filter system, oil mist extraction
- extraction arm
- chemical industry: chemical vapours, vapour return hose at loading arm, paint steam, spray mist extraction
- explosion hazard area
- animal stall, animal shed: barn ventilation
- bus, utility vehicle, caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel/ marine, yacht: ventilation, heating
- clean room ventilation, semiconductor production machine
- bellows, compensators

### Properties

- super-light weight
- highly flexible + compressible 3:1
- abrasion-resistant

- microbe resistant
- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility
- flame-retardant according to: UL94-HB
- flame-retardant according to: DIN 4102-B1
- permanently antistatic wall: in accordance with ISO 8031 electrical and surface resistance  $<10^9 \Omega$
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dust (zone 22 inside), for conveying of non-flammable liquids, for use in zone 1 and 2 (gases)
- conforms to the safety regulations of the German Wood Trade Association
- according to DIN 26057 Type 1
- conforms to RoHS guideline

### Temperature Range

- 40°C to 90°C
- short time to 125°C

### Design, Material

patented PROTAPE® tape hose

- spring steel wire integrated in wall
- wall: permanently antistatic premium ester-polyurethane (Pre-PUR®)
- wall thickness 0,4 mm approx.

### Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: partially coloured, completely coloured
- customer-specific branding
- ID 1"/25mm – 12"/305mm compressed packed in poly bag (low transportation cost / risk, minimum storage size), ID315 – 500mm not compressed

I.D. in / mm	O.D. mm	Pressure DIN 26057 (50% Elongation) bar	Vacuum DIN 26057 (axially fixed) bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
<b>standard</b>							
1,5 / 38	46	0,630 (1,86)	0,245 (0,73)	27	0,220	5 10 15	301-0038-0000
- / 40	48	0,600 (1,77)	0,235 (0,66)	28	0,230	5 10 15	301-0040-0000
1,75 / 44-45	53	0,535 (1,58)	0,210 (0,52)	31	0,255	5 10 15	301-0045-0000
2 / 50-51	58	0,480 (1,42)	0,170 (0,85)	33	0,280	5 10 15	301-0050-0000
2,36 / 60	68	0,405 (1,19)	0,145 (0,59)	38	0,340	5 10 15	301-0060-0000
2,5 / 63-65	73	0,370 (1,09)	0,130 (0,51)	40	0,360	5 10 15	301-0065-0000
- / 70	78	0,345 (1,02)	0,125 (0,44)	43	0,380	5 10 15	301-0070-0000
3 / 75-76	83	0,325 (0,95)	0,115 (0,39)	45	0,410	5 10 15	301-0075-0000
- / 80	88	0,305 (0,89)	0,110 (0,34)	48	0,440	5 10 15	301-0080-0000
3,5 / 89-90	98	0,270 (0,79)	0,095 (0,27)	53	0,490	5 10 15	301-0090-0000
4 / 100-102	108	0,245 (0,71)	0,055 (0,30)	58	0,510	5 10 15	301-0100-0000
- / 110	118	0,220 (0,65)	0,050 (0,25)	63	0,560	5 10 15	301-0110-0000
4,5 / 114-115	123	0,210 (0,62)	0,050 (0,23)	66	0,580	5 10 15	301-0115-0000
4,72 / 120	128	0,205 (0,59)	0,045 (0,21)	68	0,610	5 10 15	301-0120-0000
5 / 125-127	133	0,195 (0,57)	0,045 (0,19)	71	0,630	5 10 15	301-0125-0000
- / 130	138	0,185 (0,55)	0,040 (0,18)	73	0,660	5 10 15	301-0130-0000
5,5 / 140	148	0,175 (0,51)	0,040 (0,15)	78	0,710	5 10 15	301-0140-0000
6 / 150-152	158	0,160 (0,48)	0,035 (0,13)	83	0,760	5 10 15	301-0150-0000
6,3 / 160	168	0,150 (0,45)	0,035 (0,12)	88	0,810	5 10 15	301-0160-0000
7 / 178-180	188	0,135 (0,40)	0,030 (0,09)	98	0,900	5 10 15	301-0180-0000
8 / 200-203	208	0,120 (0,36)	0,025 (0,11)	108	1,030	5 10 15	301-0200-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.



I.D.	O.D.	Pressure DIN 26057 (50% Elongation) bar	Vacuum DIN 26057 (axially fixed) bar	Bending Radius	Weight	Dimensions in Stock	Order No.
in / mm	mm			mm	kg/m	m	
- / 225	234	0,110 (0,32)	0,020 (0,08)	122	1,160	5 10	301-0225-0000
- / 250	259	0,100 (0,29)	0,020 (0,06)	136	1,280	5 10	301-0250-0000
10 / 254	263	0,095 (0,28)	0,020 (0,06)	144	1,300	5 10	301-0254-0000
11 / 280	289	0,085 (0,26)	0,020 (0,05)	149	1,430	5 10	301-0280-0000
- / 300	309	0,080 (0,24)	0,015 (0,04)	159	1,700	5 10	301-0300-0000
12 / 305	315	0,080 (0,23)	0,015 (0,04)	163	1,730	5 10	301-0305-0000
- / 315	325	0,075 (0,23)	0,015 (0,04)	168	1,790	5 10	301-0315-0000
- / 350	360	0,070 (0,20)	0,015 (0,03)	185	2,000	5 10	301-0350-0000
- / 400	410	0,060 (0,18)	0,015 (0,02)	210	2,260	5 10	301-0400-0000
- / 450	460	0,055 (0,16)	0,010 (0,02)	235	2,520	5 10	301-0450-0000
- / 500	510	0,050 (0,14)	0,010 (0,01)	260	2,780	5 10	301-0500-0000
6,5 / 165	173	0,150 (0,43)	0,035 (0,11)	91	0,830	5 10 15	301-0165-0000
14 / 356	366	0,070 (0,20)	0,015 (0,03)	190	2,100	5 10	301-0356-0000

**neutral imprint: <ID> antistatic + microbe resistant + flame retardant <neutral batch no.>**

1,5 / 38	46	0,630 (1,86)	0,245 (0,73)	27	0,220	10	301-0038-0007
- / 40	48	0,600 (1,77)	0,235 (0,66)	28	0,230	10	301-0040-0007
2 / 50-51	58	0,480 (1,42)	0,170 (0,85)	33	0,280	10	301-0050-0007
2,36 / 60	68	0,405 (1,19)	0,145 (0,59)	38	0,340	10	301-0060-0007
2,5 / 63-65	73	0,370 (1,09)	0,130 (0,51)	40	0,360	10	301-0065-0007
- / 70	78	0,345 (1,02)	0,125 (0,44)	43	0,380	10	301-0070-0007
3 / 75-76	83	0,325 (0,95)	0,115 (0,39)	45	0,410	10	301-0075-0007
- / 80	88	0,305 (0,89)	0,110 (0,34)	48	0,440	10	301-0080-0007
4 / 100-102	108	0,245 (0,71)	0,055 (0,30)	58	0,510	10	301-0100-0007
4,72 / 120	128	0,205 (0,59)	0,045 (0,21)	68	0,610	10	301-0120-0007
5 / 125-127	133	0,195 (0,57)	0,045 (0,19)	71	0,630	10	301-0125-0007
5,5 / 140	148	0,175 (0,51)	0,040 (0,15)	78	0,710	10	301-0140-0007
6 / 150-152	158	0,160 (0,48)	0,035 (0,13)	83	0,760	10	301-0150-0007
6,3 / 160	168	0,150 (0,45)	0,035 (0,12)	88	0,810	10	301-0160-0007
7 / 178-180	188	0,135 (0,40)	0,030 (0,09)	98	0,900	10	301-0180-0007
8 / 200-203	208	0,120 (0,36)	0,025 (0,11)	108	1,030	10	301-0200-0007
- / 225	234	0,110 (0,32)	0,020 (0,08)	122	1,160	10	301-0225-0007
- / 250	259	0,100 (0,29)	0,020 (0,06)	136	1,280	10	301-0250-0007
- / 300	309	0,080 (0,24)	0,015 (0,04)	159	1,700	10	301-0300-0007

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

### Accessories



CLAMP 212



CLAMP 210 BRIDGE  
CLAMP



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 223

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.



CONNECT 270-271



Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.