

// 740AA



**Concrete pumping 85 bar (1275 psi)
Heavy duty - Steel reinforced**

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile steel cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: high pressure concrete pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	69,00	2,72	85	1275	170	2500	255,0	10,04		2,100	1,42
63,0	2 1/2"	85,00	3,35	85	1275	170	2500	315,0	12,40		3,300	2,22
76,0	3"	100,00	3,94	85	1275	170	2500	380,0	14,96		4,490	3,02
90,0	3 1/2"	116,00	4,57	85	1275	170	2500	450,0	17,72		5,430	3,65
102,0	4"	126,00	4,96	85	1275	170	2500	510,0	20,08		6,520	4,39
102,0	4"	128,00	5,04	85	1275	170	2500	510,0	20,08		6,950	4,68
127,0	5"	153,00	6,02	85	1275	170	2500	635,0	25,00		9,720	6,54
127,0	5"	155,00	6,10	85	1275	170	2500	635,0	25,00		10,250	6,89
152,0	6"	184,00	7,24	85	1275	170	2500	760,0	29,92		13,660	9,19

ALFAGOMMA ITALY **740** 85 bar (1275 psi) W.P. HEAVY DUTY CONCRETE PUMPING Ω     