

AERGEN 20 L/L

COMPRESSED AIR LONG LENGTH HOSE



APPLICATION

Delivery hose for compressed air and inert fluids

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **SBR/EPDM** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F +176°F

-30°C +80°C

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
6	1/4	14	35/64	0.18	20	300	60	900	50	MAX 100
8	5/16	17	43/64	0.25	20	300	60	900	65	MAX 100
10	3/8	19	3/4	0.29	20	300	60	900	80	MAX 100
13	1/2	23	29/32	0.40	20	300	60	900	105	MAX 50
15	19/32	25	1	0.46	20	300	60	900	120	MAX 50
16	5/8	26	1 5/16	0.48	20	300	60	900	130	MAX 50
19	3/4	30	1 3/16	0.62	20	300	60	900	150	MAX 50
25	1	37	1 29/64	0.86	20	300	60	900	200	MAX 50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT AERGEN W.P. 20 BAR D ITALY