



FOOD TYROL

Milk and fatty products delivery hose 10bar

APPLICATION / USE

Application robust delivery hose for transporting fatty liquids and beverages such as milk, olive oil, etc.

Temperature -30°C to +85°C

Features non tasting, robust yet kink resistant, minimal weight, easy cleaning, smooth lining

CONSTRUCTION

Type mandrel built

Tube oil resistant elastomer compound, white, smooth, food quality

Reinforcement high tensile textile cord

Cover blend of synthetic elastomer compound, blue, smooth with cloth impression, oil, abrasion, weather and ozone resistant

Standard/Notice conforming to FDA standards for aqueous food / sterilisation max 110°C for a short period with steam, cleaning max 40°C for a short period with cleaning agents containing max 1% peracetic acid, 2% phosphoric acid, 5% caustic soda

CODE	ID	OD	WALL	WORKING PRESSURE	BURST PRESSURE	BENDING RADIUS	WEIGHT	MAX. LENGTH
	mm	mm	mm	bar	bar	mm	kg / m	m
FOD030B-19x5.5	19	30	5,5	10	30	152	0,60	40
FOD030B-25x6	25	37	6	10	30	200	0,83	40
FOD030B-32x6	32	44	6	10	30	256	0,97	40
FOD030B-38x7	38	52	7	10	30	304	1,35	40
FOD030B-51x7	51	65	7	10	30	408	1,74	40
FOD030B-63x7	63	77	7	10	30	504	2,12	40
FOD030B-76x8	76	92	8	10	30	608	2,83	40
FOD030B-102x8	102	118	8	10	30	816	3,70	40

Other bore sizes and dimensions are available on request.