

// 350LE



Steam 6 bar (90 psi) - Hot water 15 bar (225 psi)

FDA - 3-A - arrêté du 09/11/94 D

Tube: white EPDM.

Reinforcement: high tensile textile cords.

Cover: blue EPDM - heat, abrasion and ozone resistant.

Application: saturated steam and hot water delivery in general industrial applications. Specially designed for wash down use in the food and dairy industry.

Also suitable for liquid food and alcoholic beverages.

Constant operation: water -40 °C +120 °C (-40 °F +248 °F)
steam +165 °C (+330 °F)

↔		↔		↻		↻		⌒		⌘	⌚	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	6	90	60	900				0,360	0,25
16,0	5/8"	26,00	1,02	6	90	60	900				0,420	0,29
19,0	3/4"	31,00	1,22	6	90	60	900				0,590	0,40
25,0	1"	37,00	1,46	6	90	60	900				0,740	0,50
32,0	1 1/4"	46,00	1,81	6	90	60	900				0,930	0,63
38,0	1 1/2"	52,00	2,05	6	90	60	900				1,090	0,74
51,0	2"	67,00	2,64	6	90	60	900				1,660	1,12